Statewide Interoperability Executive Committee

Standard

Arizona Interoperable Channels Plan and Priority Programming Guide

Date: 01/10/2022

This document was prepared under a grant from the Federal Emergency Management Agency's Grant Programs Directorate (FEMA/GPD) within the U.S. Department of Homeland Security. Points of view or opinions expressed in this document are those of the authors and do not necessarily represent the official position or policies of FEMA/GPD or the U.S. Department of Homeland Security

This document is reviewed annually. This document was last reviewed [01/10/2022].

Record of Changes

This Record of Changes is used to record revisions to this document, including a brief description of the changes made, the date the changes went into effect by approval of the SIEC, and the appropriate contact.

Change No.	Date	Description	Contact	
0 11/19/2013		Approval by the PSCC. Moved to new format; Added definitions and reference sections. The document had been through numerous versions between August 2010 to January 2012, however a record of changes was not available.	Glade Jarman	
1	10/31/2016	Updates to reflect sunset of the PSCC and PSIC Office and the 800 MHz Band Reconfiguration Completion.	Jeremy Knoll	
2	09/03/2019	Addition of Federal IR and LE Channels.	Morgan Hoaglin	
3	10/01/2019	Deleted Ch names older than 8 years	Morgan Hoaglin	
4	10/22/2019	Minor page formatting	Morgan Hoaglin	
5	10/28/2019	Added CTCSS on RX, as per NIFOG 1.6.1a	Morgan Hoaglin	
6	01/04/2022	Fixed IR/LE headers to correct band	Morgan Hoaglin	
7	03/01/2022	Added more information on VMED28 usage for Landing Zones (LZ)	Morgan Hoaglin	

Table of C	ontents
------------	---------

1	Introduction1
1.1	Background1
1.2	Purpose
1.3	Scope1
1.4	Definitions2
1.5	References
1.6	Administration
1.7	
1.8	Updates & Revisions
2	Subscriber Programming4
2.1	Channels
2.2	Nomenclature
2.3	Common Language Protocol 5
2.4	FCC Allocations and related Programming Requirements
2.5	Licensing Requirements5
2.6	Calling Channels
2.7	Tactical Channels
-	National VHF Interoperability Channels/Frequencies7
3	National VHF Interoperability Chamles/Frequencies
3 4	National UHF Interoperability Channels/Frequencies
4	National UHF Interoperability Channels/Frequencies7 FCC 700 MHz Public Safety Band7
4 5	National UHF Interoperability Channels/Frequencies 7 FCC 700 MHz Public Safety Band 7 700 MHz Calling Channels 9
4 5 5.1	National UHF Interoperability Channels/Frequencies 7 FCC 700 MHz Public Safety Band 7 700 MHz Calling Channels 9 Monitoring 9
4 5 5.1 5.2	National UHF Interoperability Channels/Frequencies 7 FCC 700 MHz Public Safety Band 7 700 MHz Calling Channels 9 Monitoring 9 Operations 9
4 5 5.1 5.2 5.3	National UHF Interoperability Channels/Frequencies 7 FCC 700 MHz Public Safety Band 7 700 MHz Calling Channels 9 Monitoring 9 Operations 9 Encryption 9
4 5 5.1 5.2 5.3 5.4	National UHF Interoperability Channels/Frequencies 7 FCC 700 MHz Public Safety Band 7 700 MHz Calling Channels 9 Monitoring 9 Operations 9 Encryption 9 Deployable Systems 9
4 5.1 5.2 5.3 5.4 5.5	National UHF Interoperability Channels/Frequencies 7 FCC 700 MHz Public Safety Band 7 700 MHz Calling Channels 9 Monitoring 9 Operations 9 Encryption 9 Deployable Systems 9
4 5 5.1 5.2 5.3 5.4 5.5 5.6	National UHF Interoperability Channels/Frequencies 7 FCC 700 MHz Public Safety Band 7 700 MHz Calling Channels 9 Monitoring 9 Operations 9 Encryption 9 Deployable Systems 9 Trunking on the Interoperability Channels 10
 5.1 5.2 5.3 5.4 5.5 5.6 6 7 	National UHF Interoperability Channels/Frequencies 7 FCC 700 MHz Public Safety Band 7 700 MHz Calling Channels 9 Monitoring 9 Operations 9 Encryption 9 Deployable Systems 9 Trunking on the Interoperability Channels 10 Minimum Programming Guide 11
4 5 5.2 5.3 5.4 5.5 5.6 6 7 APPE	National UHF Interoperability Channels/Frequencies 7 FCC 700 MHz Public Safety Band 7 700 MHz Calling Channels 9 Monitoring 9 Operations 9 Encryption 9 Deployable Systems 9 Trunking on the Interoperability Channels 10 Minimum Programming Guide 11 FCC 800 MHz National Interoperability Channels 11 NDIX A 1
4 5.1 5.2 5.3 5.4 5.5 5.6 6 7 APPE Ari	National UHF Interoperability Channels/Frequencies 7 FCC 700 MHz Public Safety Band 7 700 MHz Calling Channels 9 Monitoring 9 Operations 9 Encryption 9 Deployable Systems 9 Trunking on the Interoperability Channels 10 Minimum Programming Guide 11 FCC 800 MHz National Interoperability Channels 11
4 5.1 5.2 5.3 5.4 5.5 5.6 6 7 APPE Ari: VH	National UHF Interoperability Channels/Frequencies 7 FCC 700 MHz Public Safety Band 7 700 MHz Calling Channels 9 Monitoring 9 Operations 9 Encryption 9 Deployable Systems 9 Trunking on the Interoperability Channels 10 Minimum Programming Guide 11 FCC 800 MHz National Interoperability Channels 11 NDIX A 1 zona Statewide Interoperable Channel Plan - Priority Programming Guides 1
4 5.1 5.2 5.3 5.4 5.5 5.6 6 7 APPE Ari: VH UH	National UHF Interoperability Channels/Frequencies 7 FCC 700 MHz Public Safety Band 7 700 MHz Calling Channels 9 Monitoring 9 Operations 9 Deployable Systems 9 Trunking on the Interoperability Channels 10 Minimum Programming Guide 11 FCC 800 MHz National Interoperability Channels 11 NDIX A 1 F. 1 F. 1
4 5.1 5.2 5.3 5.4 5.5 5.6 6 7 APPE Ari: VH UH 800	National UHF Interoperability Channels/Frequencies 7 FCC 700 MHz Public Safety Band 7 700 MHz Calling Channels 9 Monitoring 9 Operations 9 Encryption 9 Deployable Systems 9 Trunking on the Interoperability Channels 10 Minimum Programming Guide 11 FCC 800 MHz National Interoperability Channels 11 NDIX A 1 F. 1 F. 2

List of Tables

Table 1: Non-Federal VHF National Interoperability Channels	7
Table 2: Non-Federal UHF National Interoperability Repeater Channels	8
Table 3: MESA PD 700 MHz Portable Trunked Channel Plan	10
Table 4: Minimum 700 MHz Programming Guide for Radios with Space Limitations	11
Table 5: Non-Federal 800 MHz Mutual Aid Repeater Channels	12
Table 6: Statewide VHF Priority Programming Guide	1a
Table 7: Statewide UHF Priority Programming Guide	2a
Table 8: Statewide 800 MHz Priority Programming Guide	3a
Table 9: Statewide 700 MHz Priority Programming Guide	4a
Table 10: VHF Incident Reponse (IR) Federal Interoperability Channels	5a
Table 11: VHF Law Enforcement (LE) Federal Interoperability Channels	6a
Table 12: UHF Incident Reponse (IR) Federal Interoperability Channels	7a
Table 13: UHF Law Enforcement (LE) Federal Interoperability Channels	9a

1 Introduction

1.1 Background

In 2009, the Statewide Interoperability Executive Committee (SIEC) undertook efforts to create a standard for operational and technical parameters for use of the 700 MHz public safety band. These efforts included the adoption of a Standard Channel Nomenclature and development of a prioritized list of interoperable channels. As the SIEC and their Technical and Operational Workgroup evaluated options for the creation of the Standard, the scope of work was expanded to include VHF, UHF and 800 MHz public safety bands as well. The National Public Safety Telecommunications Council (NPSTC) and the Association of Public-Safety Communications Officials (APCO) have established national standards in channel naming conventions resulting in the current ANSI Standard (ANS 1-104-2-2017). These channel naming conventions were incorporated into the Department of Homeland Security Office of Emergency Communications (DHS-OEC) National Interoperability Field Operations Guide (NIFOG). As these standards developed, they were also incorporated into Arizona's plan. The first Interoperable Channel Priority Program Guide was approved by the SIEC on October 19, 2010, with the Arizona Interoperable Channels Plan being approved by the SIEC on February 15, 2011. The latest major change is the addition of the Incident Response (IR) channels. IR channels have been licensed for usage in the state by Arizona Department of Public Safety.

1.2 Purpose

The purpose of this Plan is to establish requirements and/or recommendations for programming of statewide interoperable channels into subscriber units and to provide guidance on the use of the interoperable channels during day-to-day and emergency use. This Plan is intended to identify and prioritize interoperable channels and to establish consistent naming conventions. It is not intended to cover the operational procedures for use and monitoring.

1.3 Scope

This document provides SIEC requirements and recommendations for the VHF, UHF and 700 MHz interoperability spectrum.¹ Administration of the interoperable portion of the 800 MHz spectrum is the responsibility of the 800 MHz NPSPAC Arizona Regional Review Committee. Therefore, while 800 MHz interoperability information is included for purposes of providing a complete reference, 800 MHz users are referred to the Arizona 800 MHz Regional Plan (Region 3 PR Docket 91-143) for requirements and recommendations regarding that spectrum band.

¹ APCO/NENA General Meeting Minutes from December 9, 2005 and Arizona Statewide Interoperability Committee Meeting Minutes from January 24, 2006 mutually confirm the transfer of coordination for the VHF and UHF bands from APCO to the SIEC and SIEC acceptance of coordination planning for the interoperability channels in the VHF, UHF and 700 MHz bands.

1.4 Definitions

- AIRS: Arizona Interagency Radio System, formerly referred to as the Interagency Radio System (IARS) or as the Arizona Emergency Radio System (AERS).
- Bandwidth: The difference between the upper and lower frequencies in a continuous set of frequencies. It is typically measured in Kilohertz.
- CTCSS: Continuous Tone-Coded Squelch System is a circuit that is used to reduce the annoyance of listening to other users on a shared two-way radio communications channel. CTCSS also reduces ambient noise from opening squelch on receive. It is sometimes called tone squelch. Where more than one user group is on the same channel (called *co-channel users*), CTCSS mutes the other users if they are using a different CTCSS tone or no CTCSS.
- DPS: Department of Public Safety
- EMS: Emergency Medical Services
- FCC: Federal Communications Commission
- Hz: Hertz, the unit of frequency in the International System of Units. It is defined as the number of cycles per second of a periodic phenomenon.
- kHz: Kilohertz, one thousand Hertz
- MHz: Megahertz, one million Hertz
- NIFOG: National Interoperability Field Operations Guide
- NGO: Non-governmental Organization
- NPSTC: National Public Safety Telecommunications Council
- POC: Point of Contact
- Project 25 (P25 or APCO-25): A suite of standards for digital radio communications for use by federal, state/province and local public safety agencies in North America to enable them to communicate with other agencies and mutual aid response teams in emergencies.
- Rx: Receiving
- SIEC: The Statewide Interoperability Executive Committee (SIEC or Committee) is a stakeholder driven committee that advances interoperable communications in Arizona by providing guidance on technical and operational communication interoperability matters. The SIEC manages the interoperability portions of the 700 MHz, UHF and VHF spectrums, and has operational oversight of AIRS.
- SOP: Standard Operating Procedure

Arizona Interoperable Channels Plan and Priority Programming Guide

- Trunked radio system: a complex type of computer-controlled two-way radio system that allows sharing of relatively few radio frequency channels among a large group of users.
- Tx: Transmitting
- UHF: Ultra High Frequency
- VHF: Very High Frequency
- WSB: Arizona Department of Public Safety, Wireless Systems Bureau which licenses the frequencies used by the AIRS system and has engineering and maintenance responsibility for AIRS.

1.5 References

This document refers to naming conventions APCO/NPSTC ANS 1-104-2-2017, available online at: <u>https://www.apcointl.org/~documents/standard/11042-2017-common-channel-naming-document/?layout=default</u>

1.6 Administration

The SWIC office is responsible for administering this procedure.

1.7 Document Terminology

The terms "shall," "must," "will," and "required" are used throughout this document to indicate required parameters and to differentiate from recommended parameters. Recommendations are identified by the words "should," "desirable" and "preferably."

1.8 Updates & Revisions

This document will be reviewed annually and updated as needed. Those wishing to suggest revisions or additions to this document should send their feedback to the SWIC, electronically to swic@azdps.gov.

Revisions to this document will be reviewed by the Technical and Operational Workgroup, which will recommend appropriate changes to the SIEC. The SIEC must then approve all such changes. Revised versions of this document will be effective once approved by the SIEC.

If no revisions are required, the "last reviewed" date will be updated, and no other changes will be made.

2 Subscriber Programming

2.1 Channels

Every portable and mobile radio in Arizona should include the following channels that are within the same band of operation as the basic radio:

- All of the national interoperable channels. These channels, where possible, should be programmed in a distinctly identified area (i.e. zone, bank, deck) of each radio.
- All of the statewide channels belonging to the Arizona Interagency Radio System (AIRS). See the AIRS Standard Operating Procedures (SOP) for programming information.
- Any other statewide interoperability channels established for the radio's band of operation.

Due to space limitations in some radios, it may not be possible to program all the interoperable channels into all radios. In that case, consult the Interoperable Channel Plan for each frequency band as listed in Appendix A to find the channels prioritized for use in Arizona. Those channels are to be programmed into the radios with the highest priority first, continuing as space permits.

2.2 Nomenclature

Standard nomenclature² will be used in Arizona and channel displays will be in accordance with that nomenclature. Since simplex channels have different nomenclature than repeated channels, both must be programmed, in lieu of utilizing a Direct or Talk around Button. The channel tables provide the standard eight-character nomenclature to be used.³

The standardized format for channel names specifies a maximum length of eight characters. The first character is a spectrum band designator (i.e. L, V, U, 7 or 8). The next three or four characters signify the primary purpose of operations on the channel (i.e. CALL, DATA, FIRE, GTAC, LAW, MED, MOB, TAC or TRVL). The next one or two characters provide a unique channel identifier. Finally, a single character may be used to identify a modification to the default operation type on the channel/channel pair (i.e. "D" for direct or talk around use in simplex operations).

2.3 Common Language Protocol

To provide interoperability among first responder agencies at the local, state and national level, only plain English language shall be used when communicating on any interoperability talkgroup or channel. In order to avoid confusion or misunderstanding, 10-codes, incident codes or signals are not to be used on these talkgroups or channels.

2.4 FCC Allocations and related Programming Requirements

The listing of the FCC allocations for the narrowband interoperability spectrum and related programming requirements can be found on the Association of Public-Safety Communications Officials – International website at:

http://www.apcointl.com/new/commcenter911/documents/APCO-NPSTC-ANS1-104-1web.pdf

2.5 Licensing Requirements

The FCC designated national interoperability channels require no separate FCC license for mobile equipment. Mobile Relay (FB2) and Fixed Stations (FB) require FCC licensing.

² APCO/NPSTC ANS 1.104.1-2010: Nomenclature for the Public Safety Interoperability Channels was approved by the American National Standards Institute (ANSI) on June 9, 2010 and provides a standardized naming format for each Federal Communications Commission (FCC) and National Telecommunications and Information and Administration (NTIA) designated Interoperability Channel in the Public Safety and Federal government Radio Services.

³ In the case where radios cannot, for technical reasons, support eight character names, a six character name may be used by deleting the first band character and limiting the primary purpose designator to three characters (i.e. CAL, DAT, FIR, and GTC). The six character name may only be used in equipment that is not capable of implementing eight character names.

2.6 Calling Channels

Calling channels are used to contact other users in the region for the purpose of requesting incident-related information and assistance, and for setting up tactical communications for specific events. In most cases, the calling party will be asked to move from the calling channel to one of the tactical channels for continuing incident operations or other interoperability communication needs.

2.7 Tactical Channels

All Interoperability channels, except as specifically described by frequency band below, shall be used for conventional-only operation. Normally, users will call a communication/command center on one of the calling channels and be assigned an available tactical channel. By FCC rules, the tactical channels are to be used for coordination activity between different agencies in a mutual aid situation. Incidents requiring multi-agency participation will be coordinated over these channels by the agency controlling the incident. In the event of conflict between multiple activities, prioritized use shall occur according to the following levels:

- 1. Disasters, large scale incidents, or extreme emergencies requiring mutual aid or interagency communications.
- 2. Incidents where imminent danger exists to life or property.
- 3. Other incidents requiring the response of multiple agencies.
- 4. Pre-planned events requiring mutual aid or interagency communications.
- 5. Incidents involving a single agency where supplemental communications are needed for short term agency use.
- 6. Drills, tests and exercises.

In the event of multiple simultaneous incidents within the same priority level, interoperability channels should be allocated with the following priorities in mind:

- 1. Incidents with the greatest level of exigency (e.g., greater threat to life or property, more immediate need) have priority over less exigent incidents.
- 2. Agencies with single/limited interoperable options have priority use of those options over agencies with multiple interoperable options.
- 3. When at all possible, agencies already using an interoperable asset during an event should not be redirected to another resource.

In noninterference instances, tactical channels may be used on a case-by-case basis for emergency activities of a single agency.

3 National VHF Interoperability Channels/Frequencies

The VHF simplex tactical (TAC) channels are narrowband (12.5 kHz) by definition.

Description	Name	Rx Freq MHz	Rx CTCSS Hz	Tx Freq MHz	Tx CTCSS Hz
Calling	lling VCALL10 155.7525 CTCSS 156.7 155.7525		CTCSS 156.7		
Tactical	VTAC11	151.1375	CTCSS 156.7	151.1375	CTCSS 156.7
Tactical	VTAC12	154.4525	CTCSS 156.7	154.4525	CTCSS 156.7
Tactical	VTAC13	158.7375	CTCSS 156.7	158.7375	CTCSS 156.7
Tactical	VTAC14	159.4725	CTCSS 156.7	159.4725	CTCSS 156.7

Table 1: Non-Federal VHF National Interoperability Channels

Note: VTAC Frequencies shown below utilized VTAC simplex channels shown above. VTACS 36-38 are preferred. Frequencies shown are for programing end-user or subscriber radios. CTCSS RX=156.7 Hz, TX=136.5 Hz

Description	Name	Mobile Rx Freq MHz	MobileMobileRx CTCSS HzTx Freq MHz		Mobile Tx CTCSS Hz	
Tac Rpt	VTAC33	159.4725 CTCSS 156.7 151.1375		151.1375	CTCSS 136.5	
Tac Rpt	VTAC34	158.7375 CTCSS 156.7 154.4525		CTCSS 136.5		
Tac Rpt	VTAC35	159.4725	725 CTCSS 156.7 158.7375		CTCSS 136.5	
Tac Rpt	VTAC36	151.1375	CTCSS 156.7 159.4725		CTCSS 136.5	
Tac Rpt	VTAC37	154.4525	CTCSS 156.7	158.7375	CTCSS 136.5	
Tac Rpt	VTAC38	158.7375	CTCSS 156.7	159.4725	CTCSS 136.5	

4 National UHF Interoperability Channels/Frequencies

The UHF simplex tactical (TAC) channels are narrowband (12.5 kHz) by definition. Default operation should be CTCSS 156.7(5A) transmit and receive.

Description	NAME	RX FREQ MHz	RX CTCSS Hz	TX FREQ MHz	TX CTCSS Hz
Calling	UCALL40	453.2125	156.7	458.2125	156.7
Calling	UCALL40D	453.2125	3.2125 156.7 453.2125		156.7
Tactical	UTAC41	453.4625	156.7	458.4625	156.7
Tactical	UTAC41D	453.4625	156.7	453.4625	156.7
Tactical	UTAC42	453.7125	156.7	458.7125	156.7
Tactical	UTAC42D	453.7125	156.7	453.7125	156.7
Tactical	UTAC43	453.8625	156.7	458.8625	156.7
Tactical	UTAC43D	453.8625	156.7	453.8625	156.7

Table 2: Non-Federal UHF National Interoperability Repeater Channels

5 FCC 700 MHz Public Safety Band

The narrowband (12.5 kHz) voice and data interoperability channels are defined on a nationwide basis. There are two Calling channel sets and 30 Tactical channel sets. Channel sets are comprised of two 6.25 kHz channels each.

5.1 700 MHz Calling Channels

Users should first attempt to call in simplex mode. Use 7CALL50D as the primary calling channel and 7CALL70D as the secondary calling channel. Users should next attempt to call in repeater mode, using 7CALL50 first and then 7CALL70. In addition to the usual calling channel functions, the calling channels may be used to notify users when a priority is declared on one or more of the tactical interoperability channels.

5.2 Monitoring

700 MHz licensees will be responsible for monitoring interoperable calling channels according to operational guidelines established by the SIEC for this function.

5.3 Operations

Use the ANSI/TIA 102 Standards (i.e., Project 25 digital protocols) as the Digital Interoperability Standard for the conventional-only mode of operation on the narrowband voice & data interoperability channels⁴. The standard Network Access Code (NAC) \$293 should be used for all digital operations on FCC-designated Interoperability Channels where digital modulation is permitted or required. Mobile relay (repeater) stations that are part of a local, regional, or statewide interoperability network may be programmed with a NAC code of F7E to allow the repeater receiver to unmute.

5.4 Encryption

Use of encryption is prohibited on calling channels and permitted on all other interoperability channels. Use of encryption on interoperability channels is generally not recommended.

5.5 Deployable Systems

General Public Safety Services Channels labeled 7TAC51 through 7TAC54 and 7TAC71 through 7TAC74 shall be made available for deployable equipment used during disasters and other emergency events that place a heavy, unplanned burden upon in-place radio systems. The SIEC shall consider the need for both "deployable trunked" and "deployable conventional" systems and make those channels available to all entities in Arizona. Agencies responsible for deployable interoperability resources are encouraged to develop and facilitate the signing of a Memorandum of Understanding (MOU) with each of their interoperability partners for the use of the equipment. These MOUs will allow their interoperability partners to preprogram

⁴ Voice and Data Interoperability standards were decided in the 4th R&O in Docket 96-86 and can be found in Part 90 of the Code of Federal Regulations (CFR). Voice I/O standard documents are listed in 90.548(a)(i); data I/O standard documents are listed in 90.548(a)(ii).

Arizona Interoperable Channels Plan and Priority Programming Guide

subscriber equipment and otherwise train and prepare to use the resource during exercises, planned events and incidents.

5.6 Trunking on the Interoperability Channels

Trunking the Interoperability channels on a secondary basis shall be limited to operation on eight specific 12.5 kHz channel sets, divided into two subsets of four 12.5 kHz channels. One subset is defined by 7TAC51 through 7TAC54 and the other by 7TAC71 through 7TAC74. In Arizona, the following six channel sets are recommended for use:

12.5 kHz Channel Pair	.5 kHz Channel Pair Name		Name
23/24	7TAC51	263/264	7TAC54
103/104	7TAC52	817/818*	7TAC73*
183/184	7TAC53	897/898	7TAC74

*Subject to restrictions on the border with Mexico

The City of Mesa Police Department has requested and been approved by the SIEC for the use of the six channel sets for a 700 MHz mobile trunked system with cache radios to be utilized as an interoperable UASI asset.

Table 3: MESA PD 700 MHz Portable Trunked Channel Plan

	NAME	BANDWIDTH	RX FREQ	RX NAC	TX FREQ MHz	TX NAC
			MHz			
1	7TAC51	12.5 kHz	769.14375	3966 or \$F7E	799.14375	659 or \$293
2	7TAC51D	12.5 kHz	769.14375	3966 or \$F7E	769.14375	659 or \$293
3	7TAC52	12.5 kHz	769.24375	3966 or \$F7E	799.64375	659 or \$293
4	7TAC52D	12.5 kHz	769.24375	3966 or \$F7E	769.24375	659 or \$293
5	7TAC53	12.5 kHz	770.14375	3966 or \$F7E	800.14375	659 or \$293
6	7TAC53D	12.5 kHz	770.14375	3966 or \$F7E	770.14375	659 or \$293
7	7TAC54	12.5 kHz	770.64375	3966 or \$F7E	800.64375	659 or \$293
8	7TAC54D	12.5 kHz	770.64375	3966 or \$F7E	770. 64375	659 or \$293
9	7TAC73	12.5 kHz	774.10625	3966 or \$F7E	804.10625	659 or \$293
10	7TAC73D	12.5 kHz	774.10625	3966 or \$F7E	774.10625	659 or \$293
11	7TAC74	12.5 kHz	774.60625	3966 or \$F7E	804.60625	659 or \$293
12	7TAC74D	12.5 kHz	774.60625	3966 or \$F7E	774.60625	659 or \$293

6 Minimum Programming Guide

Since the 700 MHz band is new, equipment is expected to have the capacity to include all of the interoperability channels. In addition, all 700 MHz subscriber radios could be equipped to operate on all of the NPSPAC 800 MHz conventional mutual aid channels in analog mode per the 800 MHz channel table provided.

The table below recommends minimum programming requirements for those few 700 MHz radios with space limitations.

RECEIVE CHANNEL	TRANSMIT CHANNEL	BASE, MOBILE, OR FIXED (REPEATER OR CONTROL)	ELIGIBILITY /PRIMARY USE	NAME	LIMITATIONS (47 CFR Part 9)
760 24275	799.24375	Mobile-Fixed	Calling Channel	7CALL50	00 521(a)(1)(ii)
769.24375	SIMPLEX	Base-Fixed-Mobile	Calling Channel	7CALL50D	90.531(a)(1)(ii)
760 20275	799.39375	Mobile-Fixed	EMC	7MED65	
769.39375	SIMPLEX	Base-Fixed-Mobile	EMS	7MED65D	
	799.74375	Mobile-Fixed	General Public Safety	7TAC55	
769.74375	SIMPLEX	Base-Fixed-Mobile	Service	7TAC55D	
700 00075	799.89375	Mobile-Fixed	Fire	7FIRE63	
769.89375	SIMPLEX	Base-Fixed-Mobile	Fire	7FIRE63D	
770 24275	800.24375	Mobile-Fixed	General Public Safety	7TAC56	
770.24375	SIMPLEX	Base-Fixed-Mobile	Service	7TAC56D	
770 20275	800.39375	Mobile-Fixed	Leve Fafanaanst	7LAW61	
770.39375	SIMPLEX	Base-Fixed-Mobile	Law Enforcement	7LAW61D	
770 00275	800.99375	Mobile-Fixed	Othern Duchlie Commiss	7GTAC57	
770.99375	SIMPLEX	Base-Fixed-Mobile	Other Public Service	7GTAC57D	
772 25 625	803.25625	Mobile-Fixed		7CALL70*	00 524/->/(4)/!!)
773.25625	SIMPLEX	Base-Fixed-Mobile	Calling Channel	7CALL70D	90.531(a)(1)(ii)

Table 4: Minimum 700 MHz Programming Guide for Radios with Space Limitations

*Subject to restrictions on the border with Mexico

7 FCC 800 MHz National Interoperability Channels

The 800 MHz National Interoperability Channels have a bandwidth of 20 kHz. Default operation should be carrier squelch receive, CTCSS 156.7(5A) transmit. The calling channel, 8CALL90, is the national calling channel with a designated national CTCSS tone. 8CALL90D is it's corresponding direct or talk around channel name. The remaining channels are tactical channels.

Arizona Interoperable Channels Plan and Priority Programming Guide

RECEIVE CHANNEL	TRANSMIT CHANNEL	BASE, MOBILE, OR FIXED (REPEATER OR CONTROL)	OR FIXED / PRIMARY (REPEATER OR USE		LIMITATIONS (47 CFR Part 9)	
	806.0125	Mobile-Fixed	Any Public	8CALL90		
851.0125	SIMPLEX	Base-Fixed- Mobile	Safety Eligible	8CALL90D	90.16	
	806.5125	Mobile-Fixed	Any Public	8TAC91		
851.5125	SIMPLEX	Base-Fixed- Mobile	Safety Eligible	8TAC91D	90.16	
	807.0125	Mobile-Fixed	Any Public	8TAC92		
852.0125	SIMPLEX	Base-Fixed- Mobile	Safety Eligible	8TAC92D	90.16	
	807.5125	Mobile-Fixed	Any Public	8TAC93		
852.5125	SIMPLEX	Base-Fixed- Mobile	Safety Eligible	8TAC93D	90.16	
	808.0125	Mobile-Fixed	Any Public	8TAC94		
853.0125	SIMPLEX	Base-Fixed- Mobile	Safety Eligible	8TAC94D	90.16	

Table 5: Non-Federal 800 MHz Mutual Aid Repeater Channels⁵

⁵ See the Region 3 800 MHz Plan section Communications Requirements – Regional Interoperability for details regarding the use of these channels.

APPENDIX A

Arizona Statewide Interoperable Channel Plan - Priority Programming Guides

The Statewide Interoperability Executive Committee (SIEC) has approved these "priority programming guides" to standardize and increase interoperable communications throughout the state in the VHF, UHF, 700 and 800 MHz bands. It is suggested each agency incorporate these channels into their channel plan the next time their radios are programmed.

VHF

	NAME	BANDWIDTH	RX FREQ	RX CTCSS	TX FREQ	TX CTCSS	
			MHz	Hz	MHz	Hz	
1	VAIRS1	12.5 kHz	155.4750	CSQ	155.1900	141.3	
2	VAIRS2	12.5 kHz	155.4750	CSQ	155.1900	131.8	
3	VAIRS3	12.5 kHz	155.4750	CSQ	155.1900	110.9	
4	VAIRS4	12.5 kHz	155.4750	CSQ	155.1900	123.0	
5	VAIRS5	12.5 kHz	155.4750	CSQ	155.1900	167.9	
6	VSAR16	12.5 kHz	155.1600	CSQ	155.1600	127.3	
7	VFIRE21	12.5 kHz	154.2800	CSQ	154.2800	CSQ	
8	VMED28	12.5 kHz	155.3400	CSQ	155.3400	CSQ	
9	VLAW31	12.5 kHz	155.4750	CSQ	155.4750	CSQ	
10	VCALL10	12.5 kHz	155.7525	156.7	155.7525	156.7	
11	VTAC11	12.5 kHz	151.1375	156.7	151.1375	156.7	
12	VTAC12	12.5 kHz	154.4525	156.7	154.4525	156.7	
13	VTAC13	12.5 kHz	158.7375	156.7	158.7375	156.7	
14	VTAC14	12.5 kHz	159.4725	156.7	159.4725	156.7	
15	VTAC36*	12.5 kHz	151.1375	156.7	159.4725	136.5	
16	VTAC37*	12.5 kHz	154.4525	156.7	158.7375	136.5	

Table 6: Statewide VHF Priority Programming Guide

*NOTE: The use of tactical repeater pairs VTAC36/37 will supersede the use of VTAC11-14 since their Rx/Tx frequencies will be in use. In other words;

- VTAC36 uses the Rx of VTAC11 and the Tx of VTAC14 with a 8.335 MHz separation.

- VTAC37 uses the Rx of VTAC12 and the Tx of VTAC13 with a 4.285 MHz separation.

NOTE: VTAC33 and VTAC34 were replaced by VTAC36 and VTAC37 on January 11, 2012

NOTE: VSAR16 was formally STATE SAR or SAR NFM

VFIRE21 in Arizona is commonly used for medical landing zones (LZ).

VMED28 is the first choice for medical landing zones (LZ) under events that are primarily under federal coordination.

Radios capable of being programmed in analog, digital or mixed modes should use mixed mode for receive, where possible.

UHF

	, , , , , , , , , , , , , , , , , , , ,						
	NAME	BANDWIDTH	RX FREQ	RX CTCSS	TX FREQ	TX CTCSS	
			MHz	Hz	MHz	Hz	
1	UAIRS1	12.5 kHz	460.3750	CSQ	465.3750	141.3	
2	UAIRS2	12.5 kHz	460.3750	CSQ	465.3750	131.8	
3	UAIRS3	12.5 kHz	460.3750	CSQ	465.3750	110.9	
4	UAIRS4	12.5 kHz	460.3750	CSQ	465.3750	123.0	
5	UAIRS5	12.5 kHz	460.3750	CSQ	465.3750	167.9	
6	UAIRS_D	AIRS_D 12.5 kHz 460.3750 CSQ		460.3750	100.0		
7	UCALL40	12.5 kHz	453.2125	CSQ	458.2125	156.7	
8	UCALL40D	12.5 kHz	453.2125	CSQ	453.2125	156.7	
9	UTAC41	12.5 kHz	453.4625	CSQ	458.4625	156.7	
10	UTAC41D	12.5 kHz	453.4625	CSQ	453.4625	156.7	
11	UTAC42	12.5 kHz	453.7125	CSQ	458.7125	156.7	
12	UTAC42D	12.5 kHz	453.7125	CSQ	453.7125	156.7	
13	UTAC43	12.5 kHz	453.8625	CSQ	458.8625	156.7	
14	UTAC43D	12.5 kHz	453.8625	CSQ	453.8625	156.7	
15	MED-5D	12.5 kHz	463.1000	CSQ	463.1000	136.5	
16							

Table 7: Statewide UHF Priority Programming Guide

Radios capable of being programmed in analog, digital or mixed modes should use mixed mode for receive, where possible.

800 MHz

The regional AIRS channels, AIRS1 through AIRS5, have CTCSS tones only used in Arizona. The 8TAC91 through 8TAC94 channels are also national channels. Optionally, the channel name can be modified when used in the direct or talk around mode with the addition of "D" to the end of the channel name (for example, 8TAC92D).

	BAND-				
NAME	WIDTH	RX FREQ MHz	RX CTCSS Hz	TX FREQ MHz	TX CTCSS Hz
8AIRS1	20 kHz	851.0125	CSQ	806.0125	141.3
8AIRS2	20 kHz	851.0125	CSQ	806.0125	131.8
8AIRS3	20 kHz	851.0125	CSQ	806.0125	110.9
8AIRS4	20 kHz	851.0125	CSQ	806.0125	123.0
8AIRS5	20 kHz	851.0125	CSQ	806.0125	167.9
8CALL90	20 kHz	851.0125	156.7	806.0125	156.7
8TAC91	20 kHz	851.5125	156.7	806.5125	156.7
8TAC91D	20 kHz	851.5125	156.7	851.5125	156.7
8TAC92	20 kHz	852.0125	156.7	807.0125	156.7
8TAC92D	20 kHz	852.0125	156.7	852.0125	156.7
8TAC93	20 kHz	852.5125	156.7	807.5125	156.7
8TAC93D	20 kHz	852.5125	156.7	852.5125	156.7
8TAC94	20 kHz	853.0125	156.7	808.0125	156.7
8TAC94D	20 kHz	853.0125	156.7	853.0125	156.7
8AZTAC5 ⁺	20 kHz	851.0375	156.7	806.0375	156.7
8AZTAC5D ⁺	20 kHz	851.0375	156.7	851.0375	156.7
	8AIRS1 8AIRS2 8AIRS3 8AIRS4 8AIRS5 8CALL90 8TAC91 8TAC91D 8TAC91D 8TAC92D 8TAC92D 8TAC93D 8TAC93D 8TAC94D 8TAC94D	NAME WIDTH 8AIRS1 20 kHz 8AIRS2 20 kHz 8AIRS3 20 kHz 8AIRS4 20 kHz 8AIRS5 20 kHz 8AAL190 20 kHz 8TAC91 20 kHz 8TAC92 20 kHz 8TAC92 20 kHz 8TAC93 20 kHz 8TAC93 20 kHz 8TAC94 20 kHz 8TAC94 20 kHz 8TAC94 20 kHz 8TAC94 20 kHz	NAMEWIDTHRX FREQ MHz8AIRS120 kHz851.01258AIRS220 kHz851.01258AIRS320 kHz851.01258AIRS420 kHz851.01258AIRS520 kHz851.01258AIRS520 kHz851.01258AIRS520 kHz851.01258AIRS520 kHz851.01258TAC9120 kHz851.51258TAC91D20 kHz852.01258TAC9220 kHz852.01258TAC9320 kHz852.51258TAC9320 kHz852.51258TAC9420 kHz853.01258TAC94D20 kHz853.01258TAC94D20 kHz853.0125	NAMEWIDTHRX FREQ MHzRX CTCSS Hz8AIRS120 kHz851.0125CSQ8AIRS220 kHz851.0125CSQ8AIRS320 kHz851.0125CSQ8AIRS420 kHz851.0125CSQ8AIRS520 kHz851.0125CSQ8AIRS520 kHz851.0125CSQ8CALL9020 kHz851.0125156.78TAC9120 kHz851.5125156.78TAC91D20 kHz852.0125156.78TAC92D20 kHz852.0125156.78TAC93D20 kHz852.5125156.78TAC93D20 kHz853.0125156.78TAC94D20 kHz853.0125156.78TAC94D20 kHz853.0125156.78TAC94D20 kHz853.0125156.78AZTAC5*20 kHz853.0125156.7	NAMEWIDTHRX FREQ MHzRX CTCSS HzTX FREQ MHz8AIRS120 kHz851.0125CSQ806.01258AIRS220 kHz851.0125CSQ806.01258AIRS320 kHz851.0125CSQ806.01258AIRS420 kHz851.0125CSQ806.01258AIRS520 kHz851.0125CSQ806.01258AIRS520 kHz851.0125CSQ806.01258AIRS520 kHz851.0125CSQ806.01258CALL9020 kHz851.0125156.7806.01258TAC9120 kHz851.5125156.7806.51258TAC9220 kHz852.0125156.7857.01258TAC9220 kHz852.0125156.7807.01258TAC9320 kHz852.5125156.7807.51258TAC9320 kHz853.0125156.7808.01258TAC9420 kHz853.0125156.7808.01258TAC9420 kHz853.0125156.7808.01258TAC9420 kHz853.0125156.7808.01258TAC9420 kHz853.0125156.7808.01258AZTAC5 ⁺ 20 kHz851.0375156.7806.0375

⁺ See: Restrictions on the use of 8AZTAC5 and 8AZTAC5D

Radios capable of being programmed in analog, digital or mixed modes should use mixed mode for receive, where possible.

Restrictions on the use of 8AZTAC5 and 8AZTAC5D

The use of 8AZTAC5 and 8AZTAC5D are unique to Arizona with the approval of the Region 3 - 800 MHz Regional Planning Committee. The names of 8TAC95 and 8TAC95D were changed to 8AZTAC5 and 8AZTAC5D on January 11, 2012. These frequencies were also previously called 8TAC5 and 8TAC5D.

The 8AZTAC5 channel must be licensed. License to the 8AZTAC5D channel is provided under the same 8AZTAC5 license.

The Arizona 800 MHz Regional Plan states that all interoperability channel licensees for Mobile Relay (FB2), or Fixed Stations (FB) shall be obtained by and in the name of the entity authorized by the Arizona Regional Review Committee. Other base radios shall be licensed in the name of

the applicant agency. In accordance with FCC Report and Order General Docket 87-112, vehicular, portable, and aircraft stations using either the five National channels or the Statewide interoperability channel frequencies may operate without further FCC authorization. However, the prospective vehicular/portable/aircraft user must comply with 4.5.4 of this section. (See the Arizona Regional Review Committee's (ARRC), Arizona 800 MHz Regional Plan – Section 4.4: Application Procedures.)

The Arizona 800 MHz Regional Plan also states that use of these two frequencies is prohibited in some areas in the Counties bordering California; however, it shall be included in all portable/mobile equipment in all other areas. Use of these two frequencies in La Paz and Mohave Counties is subject to interference from a State of California transmitter located near Needles, California and use is prohibited within a 70 mile radius of the transmitter located at 34º 40' 54"N, 114º 41' 24"W. (See the Arizona Regional Review Committee's (ARRC), Arizona 800 MHz Regional Plan – Section 4.5.2.1: Monitoring Requirements.)

700 MHz

					-	
		BAND-				
	NAME	WIDTH	RX FREQ MHz	RX NAC	TX FREQ MHz	TX NAC
1	7CALL50	12.5 kHz	769.24375	3966 or \$F7E	799.24375	659 or \$293
2	7CALL50D	12.5 kHz	769.24375	3966 or \$F7E	769.24375	659 or \$293
3	7MED65	12.5 kHz	769.39375	3966 or \$F7E	799.39375	659 or \$293
4	7MED65D	12.5 kHz	769.39375	3966 or \$F7E	769.39375	659 or \$293
5	7TAC55	12.5 kHz	769.74375	3966 or \$F7E	799.74375	659 or \$293
6	7TAC55D	12.5 kHz	769.74375	3966 or \$F7E	769.74375	659 or \$293
7	7FIRE63	12.5 kHz	769.89375	3966 or \$F7E	799.89375	659 or \$293
8	7FIRE63D	12.5 kHz	769.89375	3966 or \$F7E	769.89375	659 or \$293
9	7TAC56	12.5 kHz	770.24375	3966 or \$F7E	800.24375	659 or \$293
10	7TAC56D	12.5 kHz	770.24375	3966 or \$F7E	770.24375	659 or \$293
11	7LAW61	12.5 kHz	770.39375	3966 or \$F7E	800.39375	659 or \$293
12	7LAW61D	12.5 kHz	770.39375	3966 or \$F7E	770.39375	659 or \$293
13	7GTAC57	12.5 kHz	770.99375	3966 or \$F7E	800.99375	659 or \$293
14	7GTAC57D	12.5 kHz	770.99375	3966 or \$F7E	770.99375	659 or \$293
15	7CALL70	12.5 kHz	773.25625	3966 or \$F7E	803.25625	659 or \$293
16	7CALL70D	12.5 kHz	773.25625	3966 or \$F7E	773.25625	659 or \$293

Table 9: Statewide 700 MHz Priority Programming Guide

Radios capable of being programmed in analog, digital or mixed modes should use mixed mode for receive, where possible.

Federal Interoperability Incident Response (IR) and Law Enforcement (LE) Tables 10-13

The authorization and usage of the Federal IR and LE channels are outlined by Memorandum of Understanding (MOU) between the U.S. Department of Interior and the Arizona Department of Public Safety. The intent of the MOU is to provide for interoperable frequencies between Federal and State, Tribal, County or Local agencies. FCC Licenses for usage within The State of Arizona have been granted and are on file with the DPS Wireless Systems Bureau. The Federal IR and LE channels are not to be used for any routine or administrative uses as defined by the National Telecommunications and Information Administration (NTIA). Frequency coordination or deconfliction shall be done through the Statewide Interoperability Coordinator (SWIC) or designee.

Agencies within Arizona are encouraged to program Federal IR and LE channels since they offer expansive interoperability when the need to communicate with various levels of the Federal Government is present.

Assignment	NAME	Note	Mobile RX	Mobil TX
Incident Calling	NC1	Calling	169.53750	164.71250
Incident Command	IR1	Repeater Pair	170.01250	165.25000
Medical Evacuation Control	IR2	Repeater Pair	170.41250	165.96250
Logistics Control	IR3	Repeater Pair	170.68750	166.57500
Interagency Convoy	IR4	Repeater Pair	173.03750	167.32500
Incident Calling Direct	IR5	Direct for NC1	169.53750	169.53750
Incident Command Direct	IR6	Direct for IR1	170.01250	170.01250
Medical Evacuation Control Direct	IR7	Direct for IR2	170.41250	170.41250
Logistics Control Direct	IR8	Direct for IR3	170.68750	170.68750
Interagency Convoy Direct	IR9	Direct for IR4	173.03750	173.03750

Table 10: Arizona Licensed VHF IR Federal Interoperability Channels

VHF Incident Response (IR) Federal Interoperability Channels

Default operations should be carrier squelch receive and **CTCSS 167.9 Hz** TX. If the user can enable/disable CTCSS on RX, **CTCSS 167.9 Hz** on RX is encouraged. All Channels are analog and NARROWBAND only.

VHF Law Enforcement (LE) Federal Interoperability Channels

Table 11: Arizona Licensed VHF (LE) Federal Interoperability Channels

Description	NAME	Note	Mobile RX	Mobile TX	CTCSS or NAC
Calling	LE A	Analog	167.08750	167.0875 (S)	167.9 Tx, CSQ Rx
Tactical	LE 1	Analog	167.08750	162.08750	167.9 Tx, CSQ Rx
Tactical	LE 2	Digital	167.25000	162.26250	\$68F (167910)
Tactical	LE 3	Digital	167.75000	162.83750	\$68F (167910)
Tactical	LE 4	Digital	168.11250	163.28750	\$68F (167910)
Tactical	LE 5	Digital	168.46250	163.42500	\$68F (167910)
Tactical	LE 6	Digital Direct for LE2	167.25000	167.25000 (S)	\$68F (167910)
Tactical	LE 7	Digital Direct for LE3	167.75000	167.75000 (S)	\$68F (167910)
Tactical	LE 8	Digital Direct for LE4	168.11250	168.11250 (S)	\$68F (167910)
Tactical	LE 9	Digital Direct for LE5	168.46250	168.46250 (S)	\$68F (167910)

Analog default operations should be carrier squelch receive and CTCSS 167.9 Hz TX (LE A and LE 1). If the user can enable/disable CTCSS on RX, CTCSS 167.9 Hz on RX is encouraged. All Channels are NARROWBAND only.

Channels shown with NAC code of \$68F are P25 Digital (LE 2 – LE 9). Digital default operations will use the NTIA Interoperability NAC code of \$68F.

UHF Incident Response (IR) Federal Interoperability Channels

Assignment	NAME	Note	Mobile RX	Mobile TX
Incident Calling	NC 2	Calling	410.23750	419.23750
Ad hoc	IR 10	Repeater Pair	410.43750	419.43750
Ad hoc	IR 11	Repeater Pair	410.63750	419.63750
SAR Incident Command	IR 12	Repeater Pair	410.83750	419.83750
Ad hoc	IR 13	Direct	413.18750	413.18750 (S)
Interagency Convoy	IR 14	Direct	413.21250	413.21250 (S)
Interagency Calling Direct	IR 15	Direct for NC2	410.23750	410.23750 (S)
Ad hoc (Direct)	IR 16	Direct for IR 10	410.43750	410.43750 (S)
Ad hoc (Direct)	IR 17	Direct for IR 11	410.63750	410.63750 (S)
SAR Incident Command Direct	IR 18	Direct for IR 12	410.83750	410.83750 (S)

Table 12: Arizona Licensed UHF (IR) Federal Interoperability Channels

Default analog operations should be carrier squelch receive and **CTCSS 167.9** Hz TX. If the user can enable/disable CTCSS on RX, **CTCSS 167.9** Hz on RX is encouraged. All Channels are **analog** and NARROWBAND only.

UHF Incident Response (LE) Federal Interoperability Channels

Table 13: Arizona Licensed UHF (LE) Federal Interoperability Channels

Description	NAME	Note	Mobile RX	Mobile TX	CTCSS or NAC
Calling	LE B	Analog	414.03750	414.03750 (S)	167.9 Tx CSQ Rx
Tactical	LE 10	Analog	409.18750	418.98750	167.9 Tx CSQ Rx
Tactical	LE 11	Repeater Pair	410.18750	419.18750	\$68F (167910)
Tactical	LE 12	Repeater Pair	410.61250	419.61250	\$68F (167910)
Tactical	LE 13	Direct	414.06250	414.06250	\$68F (167910)
Tactical	LE 14	Direct	414.31250	414.31250	\$68F (167910)
Tactical	LE 15	Direct	414.33750	414.33750	\$68F (167910)
Tactical	LE 16	Direct Analog LE 10	409.98750	409.98750	167.9 Tx CSQ Rx
Tactical	LE 17	Direct for LE 11	410.18750	410.18750	\$68F (167910)
Tactical	LE 18	Direct for LE 12	410.61250	410.61250	\$68F (167910)

Analog default operations should be carrier squelch receive and CTCSS 167.9 Hz TX (LE B and LE 10). If the user can enable/disable CTCSS on RX, CTCSS 167.9 Hz on RX is encouraged. All Channels are NARROWBAND only.

Channels shown with NAC code of \$68F are P25 Digital. Digital default operations will use the NTIA Interoperability NAC code of \$68F.